moooi

Serpentine Light



Serpentine Light by Front is an elegant suspension lamp with an airy design inspired by the twists and turns of paper. Its flowing, translucent form creates the illusion of an endless upward spiral, diffusing light evenly for a soft, natural glow. Ideal for dining tables, hallways, or offices, it adds a touch of perpetual movement to any space. Also available in a larger size (68x68x78 cm).

Detailing




Colours

Serpentine light is a fun and simple looking design created with elaborate twists and turns.

White

Serpentine Light / 8 Large

Dimensions



Technical CE

MATERIAL Shade from printed non-woven PES, coated steel pendant

81cm | 31.9

LIGHTSOURCE TYPE

LED Bulb

NUMBER OF LIGHTSOURCES

FREQUENCY 50/60

LAMPHOLDER E27

LIFETIME 15000 hours

CABLE LENGTH 250cm | 98.4"

снвом х 0.4361

COLOUR TEMPERATURE 2700 K (max)

All directions

R9

64

Product

width 68cm | 26.8" неight 81cm | 31.9" depth 68cm | 26.8" weight netto 0.7kg | 1.54lbs

Packaging

width 83cm | 32.7" Height 83.5cm | 32.9" CUBAGE 0.58m³ | 20.31ft³ LENGTH 83cm | 32.7" WEIGHT 4kg | 8.82lbs

LIGHTSOURCE INCLUDED Yes

INPUT VOLTAGE 220-240∨

max power consumption 11W

RECOMMENDED LIGHTSOURCE LED Bulb up to 20W

CABLE COLOUR Black

CANOPY Pebble II Black, ABS

снвом у 0.4114

CRI 95

LIGHT OUTPUT 1158 lm

DIMMING & LIGHTING CONTROL Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.


Technical UL

MATERIAL Shade from printed non-woven PES, coated steel pendant

LIGHTSOURCE TYPE	LIGHTSOURCE INCLUDED
LED Bulb	Yes
NUMBER OF LIGHTSOURCES	INPUT VOLTAGE 110-130V
FREQUENCY 60	MAX POWER CONSUMPTION
LAMPHOLDER	RECOMMENDED LIGHTSOURCE
E26	UL Listed SBLED Bulb up to 23W
LIFETIME	CABLE COLOUR
25000 hours	Black
CABLE LENGTH	CANOPY
250cm 98.4"	Pebble II Black, ABS
снгом х	снгом у
0.4361	0.4114
COLOUR TEMPERATURE	с яі
2700 K (max)	95
LIGHT DIRECTION	LIGHT OUTPUT
All directions	1158 lm
R9	DIMMING & LIGHTING CONTROL
64	Mains dimmable with compatible light source
	See last page for more information about the dimming possibilities.

Serpentine Light / 8 Small

Dimensions



Product

width 46cm | 18.1" неіднт 60cm | 23.6" дертн 46cm | 18.1" weight netto 0.3kg | 0.66lbs

Packaging

width 67cm | 26.4" Height 68cm | 26.8" Cubage 0.31m³ | 10.78ft³ Length 67cm | 26.4" weight 4kg | 8.82lbs

Technical CE

MATERIAL

Shade from printed non-woven PES, coated steel pendant

LIGHTSOURCE TYPE	LIGHTSOURCE INCLUDED
Incandescent	Yes
NUMBER OF LIGHTSOURCES	INPUT VOLTAGE
1	220-240V
FREQUENCY	MAX POWER CONSUMPTION
50/60	11W
LAMPHOLDER	RECOMMENDED LIGHTSOURCE
E27	LED Bulb up to 20W
LIFETIME	CABLE COLOUR
15000 hours	Black
CABLE LENGTH	CANOPY
250cm 98.4"	Pebble II Black, ABS
СНВОМ Х	CHROM Y
0.46	0.42
COLOUR TEMPERATURE	CRI
2700 K (max)	85
LIGHT DIRECTION	LIGHT OUTPUT
All directions	1137 lm
DIMMING & LIGHTING CONTROL	

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.

Technical UL

MATERIAL Shade from printed non-woven PES, coated steel pendant

LIGHTSOURCE TYPE Incandescent	LIGHTSOURCE INCLUDED
NUMBER OF LIGHTSOURCES	input voltage 110-130V
FREQUENCY 60	MAX POWER CONSUMPTION
LAMPHOLDER	RECOMMENDED LIGHTSOURCE
E26	UL Listed SBLED Bulb up to 23W
LIFETIME	CABLE COLOUR
25000 hours	Black
CABLE LENGTH	Canopy
250cm 98.4"	Pebble II Black, ABS
снгом х	снгом у
0.46	0.41
COLOUR TEMPERATURE	CRI
2700 K (max)	95
LIGHT DIRECTION	Light output
All directions	970 lm
DIMMING & LIGHTING CONTROL	

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.



Technical

MATERIAL

Shade from printed non-woven PES, coated steel pendant

Dimming & Lighting Control

Mains dimmable with compatible light source

Compatible models: 8 Large CCC, 8 Large CE, 8 Large UL, 8 Small CCC, 8 Small CE, 8 Small UL